



Item Number	Bore	Outer Diameter	Width	Load Rating Dynamic	Load Rating Static	Weight
Open	mm	mm	mm	kN	kN	kg
6800	10	19	5	1.83	0.93	0.005
6801	12	21	5	1.92	1.04	0.006
6802	15	24	5	2.08	1.26	0.007
6803	17	26	5	2.81	1.72	0.008
6804	20	32	7	4.00	2.47	0.019
6805	25	37	7	4.30	2.95	0.022
6806	30	42	7	4.70	3.65	0.026
6807	35	47	7	4.90	4.05	0.029
6808	40	52	7	5.10	4.40	0.033
6809	45	58	7	6.40	5.65	0.04
6810	50	65	7	6.60	6.10	0.052
6900	10	22	6	2.70	1.27	0.009
6901	12	24	6	2.89	1.46	0.011
6902	15	28	7	4.10	2.06	0.016
6903	17	30	7	4.65	2.58	0.018
6904	20	37	9	6.40	3.70	0.036
6905	25	42	9	7.05	4.55	0.042
6906	30	47	9	7.25	5.00	0.048
6907	35	55	10	11.20	7.45	0.074
6908	40	62	12	14.60	10.20	0.11
6909	45	68	12	15.10	11.20	0.128
6910	50	72	12	15.60	12.20	0.132